



The Compact Fluorescent Lamp with integral electronic control gear



- Supply Voltage – 220-240V/50-60Hz
  - High Efficacy – up to 50% energy saving compared with incandescents
  - Eight times the life of incandescents – average life up to 8000 hours\*
  - ELR 7W/9W/13W GU10 base for direct replacement of Halogen GU10 lamp
  - Excellent colour rendering
  - Switching does not reduce lamp life
  - Reliable starting down to -10°C
  - Lumen Maintenance – min. 80% at 2000 hours
  - Power Factor – around 0.6
- \* tested according to IEC969

Applications:

ELX GX53 specially suitable for ceiling lights, cabinet lights, downlights, etc



| Model   | Lamp<br>Wattage | Supply<br>Voltage | Luminous<br>Flux | Rendering<br>Index | Base | Size<br>DxH | Rated<br>Avg. Life | Standard<br>Pack |
|---------|-----------------|-------------------|------------------|--------------------|------|-------------|--------------------|------------------|
|         | <b>W</b>        | <b>V/Hz</b>       | <b>L m</b>       | <b>R a</b>         |      | <b>m m</b>  | <b>h</b>           | <b>p c s</b>     |
| ELR 7W  | 7               | 220-240           | 170              | 80                 | GU10 | 50x82       | 8000               | 1/10/100         |
| ELR 9W  | 9               | 220-240           | 220              | 80                 | GU10 | 50x82       | 8000               | 1/10/100         |
| ELR 13W | 13              | 220-240           | 250              | 80                 | GU10 | 50x82       | 8000               | 1/10/100         |
| ELX 7W  | 7               | 220-240           | 210              | 80                 | GX53 | 74x26       | 8000               | 1/10/100         |
| ELX 9W  | 9               | 220-240           | 280              | 80                 | GX53 | 74x26       | 8000               | 1/10/100         |

- Colour Temperature - Warmwhite, Coolwhite and Daylight are available
- LUXMAN CFL ELR, ELX lamps are not suitable for dimming and use with electronic switches
- Use indoors, or outdoors in enclosed and ventilated luminaires