

The Metal Halide Lamps



Tubular, Clear, Ignitor required

Model	Rated Lamp Wattage W	Lamp Current A	Luminous Flux L m	Diameter Avg. D m m	Length L max. m m	Base	Average Life h	Standard Pack pcs	Burning Position
MH T 70	70	0.9	5600	38	156	E27	10000	1/50	Universal
MH T 100	100	0.9	7200	38	156	E27	10000	1/50	Universal
MH T 150	150	1.6	11000	46	210	E27	10000	1/20	Universal
MH T 250	250	2.15	21000	46	259	E40	10000	1/20	Universal
MH T 400	400	3.25	37000	46	286	E40	10000	1/20	Universal
MH T 1000	1000	4.1	110000	75	385	E40	10000	1/20	p60

- Colour Temperature: 3000K, 4000K, 5000K
- Colour Rendering Index: Ra70

Elliptical, Clear, Ignitor required

Model	Rated Lamp Wattage W	Lamp Current A	Luminous Flux L m	Diameter Avg. D m m	Length L max. m m	Base	Average Life h	Standard Pack pcs	Burning Position
MH E 70	70	0.9	5500	55	140	E27	10000	1/50	Universal
MH E 100	100	0.9	7100	55	140	E27	10000	1/50	Universal
MH E 150	150	1.6	11000	55	140	E27	10000	1/20	Universal
MH E 250	250	2.15	20500	90	220	E40	10000	1/20	Universal
MH E 400	400	3.25	36000	120	280	E40	10000	1/10	Universal
MH E 1000	1000	4.1	110000	180	380	E40	10000	1/6	h45

- Colour Temperature: 4000K, 5000K
- Colour Rendering Index: Ra70