



12V Dichroic* Halogen Reflector Lamp



- Constant Luminous intensity for the entire life
- Constant colour for the entire life
- Long Life
- Crisp light and excellent colour rendering
- Dichroic reflector decreases the heat amount in the light by 62%
- Colour Temperature approx. 3000K



GU5.3/ GU4



GZ5.3/ GZ4



Model	Lamp Wattage W	Lamp Voltage V	Beam Angle	Luminous Intensity cd	Rated Avg. Life h	Base	Standard Pack pcs
MR16 EZX	20W	12	7°	8200	3000	GU5.3/GX5.3	1/10/200
MR16 ESX	20W	12	12°	3350	3000	GU5.3/GX5.3	1/10/200
MR16 BBF	20W	12	24°	950	3000	GU5.3/GX5.3	1/10/200
MR16 BAB	20W	12	36°	525	3000	GU5.3/GX5.3	1/10/200
MR16 FRB	35W	12	12°	8000	3000	GU5.3/GX5.3	1/10/200
MR16 FRA	35W	12	20°	3800	3000	GU5.3/GX5.3	1/10/200
MR16 FMW	35W	12	38°	1450	3000	GU5.3/GX5.3	1/10/200
MR16 EXT	50W	12	12°	12500	3000	GU5.3/GX5.3	1/10/200
MR16 EXZ	50W	12	24°	4400	3000	GU5.3/GX5.3	1/10/200
MR16 ENL	50W	12	30°	2350	3000	GU5.3/GX5.3	1/10/200
MR16 EXN	50W	12	38°	1750	3000	GU5.3/GX5.3	1/10/200
MR16 FNV	50W	12	60°	750	3000	GU5.3/GX5.3	1/10/200
MR16 EYF	75W	12	14°	12300	2000	GU5.3/GX5.3	1/10/200
MR16 EYJ	75W	12	24°	4600	2000	GU5.3/GX5.3	1/10/200
MR16 EYC	75W	12	38°	2000	2000	GU5.3/GX5.3	1/10/200
MR11 FTB	20W	12	10°	3900	3000	GU4/GZ4	1/10/200
MR11 FTC	20W	12	20°	1550	3000	GU4/GZ4	1/10/200
MR11 FTD	20W	12	30°	600	3000	GU4/GZ4	1/10/200
MR11 FTE	35W	12	10°	5850	3000	GU4/GZ4	1/10/200
MR11 FTF	35W	12	20°	2750	3000	GU4/GZ4	1/10/200
MR11 FTH	35W	12	30°	1300	3000	GU4/GZ4	1/10/200

• Options: BA15d base, UV STOP, 5000 hours life, Frosted Bulb, Coloured Glass Cover: Red, Yellow, Green, Blue, Purple

* Aluminium coating is also available. No light can escape from the rear of the Aluminium coated reflector